



## Series 5 Vinyl Side-Load Single Hung Window


2- and 3-lite sliders and picture windows are available

- Removable bottom sash.
- Industry leading .01 cfm/ft. air infiltration performance.
- Multi-cavity vinyl lineals improve thermal performance and enhanced sound absorbency.
- Insulating glass provides energy saving thermal efficiency.
- Fusion welded frame and sash minimizes air and water infiltration and enhances overall durability.
- Sweep lock helps provide a weather-tight seal and added security.
- Block and Tackle balance system for ease of operation.
- Removable operable sash includes full-length interlock and bottom weather reflector.
- Dual screw boss, metal reinforced meeting rail provides added strength.
- Custom sized to the nearest 1/8".
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside.
- Versatile half-screen installed from the inside or outside.\*
- Sloped sill reduces air infiltration and accommodates easy water run-off.
- Built-in accessory channels accommodate multiple installation options.
- DP-50 rating (window size tested 36" x 96").
- Jamb depth: 2.625".
- **Transferable Limited Lifetime Warranty.**

### Optional Features

- Low-E glass.
- Low-E glass with argon gas.
- Ultra Low-E glass with argon gas.
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids.
- Custom sizes.
- Factory mulling of twins and triples.
- Safety latch for sash restriction (field applied).

#### Color Options\*\*



Scan to  
experience  
our website.



ENERGY STAR compliance  
available in all series. Verify  
product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

\* Screens are not meant to restrain a child from falling through an open window.

\*\* Printing process may affect color shown.

Please refer to actual window sample when selecting colors.

