



Series 90 Double Hung Window

2- and 3-lite sliders and picture windows are available

- Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance.
- DP-60 rating (window size tested 36" x 74").
- Low-E glass with argon gas keeps indoor temperatures comfortable and consistent.
- External accessory groove accommodates nail fin option.
- Full interlocking lock and meeting rail.
- Beveled mainframe offers a classic exterior appearance.
- Fusion-welded sashes and frame add strength and boost thermal performance.
- Dual low profile, positive-action cam locks increase security (2 locks standard at 27 1/4" or wider).
- 3/4" constant force coil balance permits easy sash movement.
- Sloped sill reduces air infiltration and allows for easy water runoff.
- Rubber bulb seal helps block outside air.
- Dual push-button night latches provide optimum ventilation.
- Full screen is supported by a strong extruded aluminum frame.*
- Full vinyl sash dam on sill and high-performance weather stripping protect against air infiltration.
- Integrated, slim line lift rail allows for smooth sash operation.
- 4 1/4" frame thickness enhances appearance as well as structural integrity.
- Jamb depth is 3.25".
- **Transferable Limited Lifetime Warranty.**
- **Lifetime Glass Breakage Warranty** ensures the longevity of your windows.

Optional Features

- Low-E glass.
- Ultra Low-E glass with argon gas.
- Triple-pane, R-5 compliant glass with Low-E glass with argon gas or Ultra Low-E glass with argon gas.
- InsulKor multi-cavity foam-filled frame injections.
- Nail fin accessory for use in remodeling or new construction applications.
- 1 1/8" simulated divided lite (SDL) grid.
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids.
- Obscure or double-strength glass.
- Factory mulling of twins and triples.



**InsulKor™
Technology**




Scan to watch a video about our Series 90.

Color Options**



Lock Options**



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.
 * Screens are not meant to restrain a child from falling through an open window.
 ** Printing process may affect color shown. Please refer to actual window sample when selecting colors.
 *** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

